

ETATRACK active 2500-A-30

Single-axis Tracking System for PV Modules

Characteristics

- total module surface up to c. 26 m²
- no failure-prone light sensor
- no unnecessary tracking movements
- low power consumption (c. 2 kWh/year)
- statics according to German and European standards
- high reliability and life-expectancy
- excellent serviceability
- cost-efficient tracking system

Application

- single-axis tracking system for PV modules*
- additional energy yield of up to 40 % compared to fixed installations



Design

Tracking Unit


- single-axis tracking system
- angle of second axis 30° other angles on request
- elevation East-West: 90°
- module surface up to c. 26 m² max. dimensions of mounted frames (supportive area, installation area PV modules): width: 4.4 m, height: 5.9 m, up to four rows of PV modules in upright position
- frame and supports: steel, hot-dip Zn-coated
- screw set: steel, Zn-coated
- module clamps made of stainless steel for mounting the PV modules using the holes in the module frame, incl. M6 stainless steel screw kits
- suitable for high wind speeds: statics according to German and European standards
- suitable for ground level installation
- low energy consumption c. 2 kWh/year
- maintenance-free

Control

- electronics incl. battery in plastic housing
- supply voltage: 12V DC (nominal voltage) up to 50V_{oc} (open-circuit voltage), by one of the tracked modules**
- stepwise tracking, depending on the daily sunshine duration (length of day)
- South position in darkness
- synchronisation of multiple units possible
- standby mode in periods of low irradiation***

Drive

- DC linear drive
- maintenance-free



Foundation

- concrete foundation with steel reinforcement min. 5.3 m³

Storage and Operating Conditions

- ambient temperature range: -25 °C to +50 °C
- daily average ambient humidity: max. 80 %
- air salinity: max. 2 µg/m³, or distance from coast: min. 1 km
- altitude: -400 m to +3,000 m MSL
- for detailed description of ambient conditions for safe operation, cf. installation manual
- designs for other conditions on request

Included in Delivery

- kit tracking unit
- module clamps (cf. design): 80 sets per tracking unit for 20 PV modules
- control
- drive
- installation manual
- optional: mounting clamps (J-clips), 48 sets per tracking unit, for mounting the PV modules with middle and end clamps

* for framed PV modules according to IEC 61215, UL 1703

** for safe operation in specific system designs, an additional PV module (10 or 20Wp) might be necessary, cf. installation manual

*** for safe operation, cf. installation manual

To find out more visit www.lorentz.de

BERNT LORENTZ GmbH & Co. KG

Kroegerskoppel 7, 24558 Henstedt-Ulzburg, Germany

Tel. +49 (0) 4193 7548 - 0, Fax - 29, www.lorentz.de

Errors excepted and possible alterations without prior notice.

Sun. Water. Life.